



K1000 BACKPACK FIRE PUMP QUICK OPERATING GUIDE



Step-by-Step Operating Guide

- **Prepare the Tank**

Remove the filler cap and pour clean water through the mesh debris screen to help prevent blockages. Do not add foam or other fluids into the water tank other than freshwater for the intent of fire prevention and control.

- **Attach Spray Nozzle**

Align the quick-connect fitting on the spray hose with the outlet fitting on the pump. Push the connector firmly onto the fitting until it clicks into place. Gently pull back on the hose to confirm it is securely locked.

- **Fit the Harness**

Secure shoulder strap to the bottom of the fire pump by slotting the black fitting into the slot at the bottom of the unit. Put the backpack on, adjust the padded shoulder straps, and secure the chest belt so the unit stays comfortably on your shoulders.

- **Prime and Pump**

Grip the hand pump handle and use smooth push-and-pull strokes until water begins flowing.

- **Discharge**

Direct the stream at the base of the fire or glowing embers. Twist the adjustable nozzle to change from a focused stream for maximum reach to a cone-shaped spray for broader coverage.

Maintenance and Care

- **Inspection**

Regularly inspect the hose for cracks, check all fittings for leaks, and ensure the pump O-rings remain clean and lightly lubricated.

- **Storage**

Empty the tank completely after every use and rinse thoroughly with clean water. Never leave foam solution in the tank, as residue can damage pump components. Hang the unit upside down to drain and dry before storing it indoors away from direct sunlight and freezing temperatures.

Premium Tool & Abrasives Co. Ltd.
10761 181 Street, NW
Edmonton, Alberta, Canada
T5S 1N3

Telephone: 780.438.6576
Fax: 780.436.4103

e-mail: pta@premiumtool.com

FOR OTHER PRODUCT CATALOGUES,
ASSISTANCE OR A DISTRIBUTOR IN YOUR AREA,
PLEASE CALL:

1 800 661 6576

Find us online at: www.premiumtool.com